



In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser

N35U143U14B - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	2297
Lamp category	LED	Mountings	Suspension
Power (W)	46W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 76
Beam angle C90-270 (°) 64



Beam Angle DIR:	
E(l ×)	D(m)
828	1.25
207	2.50
92	3.76
52	5.01
33	6.26
	E(lx) 828 207 92 52

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	3.19
Length (mm)	1405

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Power supply rose 08.0031.00



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 35 mm 08.9056.06



Metal cover. Suspension Up & Down. 35 mm (Colour Black) 08.9056.NS



Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02



Metal cover. Suspension Up & Down. 35 mm (Colour White)

