


115
35
38



In-Finity 35 Suspension Up & Down 4000K General Lighting Dali

■ N35U114G14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2306 |
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 36.5W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 110 |
| Beam angle C90-270 (°) | 110 |



Beam Angle DIR: 107°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 523 | 2.63 |
| 2 | 131 | 5.26 |
| 3 | 58 | 7.90 |
| 4 | 33 | 10.53 |
| 5 | 21 | 13.16 |

Luminous flux luminaire
2306 lm

Electrical

| | | | |
|-----------------------|---------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|--------------------|-------|
| Color | Black |
| Orientation | Fixed |
| Weight (kg) | 2.56 |
| Length (mm) | 1125 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 4000K General Lighting Dali



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00



Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS



Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02



Metal cover. Suspension Up & Down.
35 mm
08.9056.06



Metal cover. Suspension Up & Down.
35 mm (Colour White)
08.9056.40



Power supply rose. Dali
08.0031.00.DA



Suspension kit
08.0030