


115
35
38



In-Finity 35 Suspension Up & Down 4000K General Lighting Dali

■ N35U144G02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	2883
Lamp category	LED	Mountings	Suspension
Power (W)	46W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Luminous flux luminaire
2883 lm

Beam Angle DIR: 107°

h(m)	E(lx)	D(m)
1	654	2.63
2	164	5.26
3	73	7.90
4	41	10.53
5	26	13.16

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.19
Length (mm)	1405

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 4000K General Lighting Dali



5



5



Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02

Metal cover. Suspension Up & Down.
35 mm (Colour White)
08.9056.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00



5



5



Metal cover. Suspension Up & Down.
35 mm
08.9056.06

Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS

Suspension kit
08.0030



Power supply rose. Dali
08.0031.00.DA