


■ N35U084G02B - Anodized Grey

Main specifications

Number of heads	1	Net lumen (lm)	1730
Lamp category	LED	Mountings	Suspension
Power (W)	16.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Beam Angle DIR: 107°

h(m)	E(lx)	D(m)
1	393	2.63
2	98	5.26
3	44	7.90
4	25	10.53
5	16	13.16

Luminous flux lumineuse
1730 lm

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable

Emergency	Without
Insulation class	I

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	1.92
Length (mm)	845

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 4000K General Lighting



5

Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02



5


Metal cover. Suspension Up & Down.
35 mm (Colour White)
08.9056.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00



Suspension kit
08.0030



5

Metal cover. Suspension Up & Down.
35 mm
08.9056.06



5

Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS



Power supply rose
08.0031.00