





In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

■ **N35U194U30BDA - White**

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.



115
35
38




Main specifications

Number of heads	1	Net lumen (lm)	3482
Lamp category	LED	Mountings	Suspension
Power (W)	66W	Environment	Indoor
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Luminous flux luminaire
3482 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		

Physical

Color	White
Orientation	Fixed
Weight (kg)	4.48
Length (mm)	1970

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali



5



5

500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam
08.0112.00

Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02

Metal cover. Suspension Up & Down.
35 mm
08.9056.06



5



Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS

Power supply rose. Dali
08.0031.00.DA

Suspension kit
08.0030



5

Metal cover. Suspension Up & Down.
35 mm (Colour White)

