


115
35
38



In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser

■ N35U114U14B - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	1990
Lamp category	LED	Mountings	Suspension
Power (W)	36.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Luminous flux luminaire
1990 lm

Beam Angle DIR: 75°

h(m)	E(lx)	D(m)
1	717	1.25
2	179	2.50
3	80	3.76
4	45	5.01
5	29	6.26

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	2.56
Length (mm)	1125

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 4000K Micro-Prismatic Diffuser



5

Metal cover. Suspension Up & Down.
35 mm (Colour White)
08.9056.40



Suspension kit
08.0030



5

Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0112.00



5

Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS



5

Metal cover. Suspension Up & Down.
35 mm
08.9056.06



Power supply rose
08.0031.00