



## In-Finity 35 Suspension Up & Down Emergency 3000K General Lighting Dali

### ■ N35UEM3G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

#### Main specifications

Number of heads	1	Net lumen (lm)	2663
Lamp category	LED	Mountings	Suspension
Power (W)	46W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

#### Optical

Lighting type	Indirect, Direct	Beam angle C90-270 (°)	110
LED type	Top LED		
Light distribution	Symmetric		
Optical type	Diffused light		
Beam angle (°)	110		

#### Electrical

Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	With		

#### Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.19
Length (mm)	1405

#### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down Emergency 3000K General Lighting Dali



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0109.00



Metal cover. Suspension Up & Down.  
35 mm  
08.9056.06



Metal cover. Suspension Up & Down.  
35 mm (Colour Black)  
08.9056.NS



Power supply rose. Dali  
08.0031.00.DA



Metal cover. Suspension Up & Down.  
35 mm (Colour Anodized Grey)  
08.9056.02



Metal cover. Suspension Up & Down.  
35 mm (Colour White)  
08.9056.40



Suspension kit  
08.0030