


115
35
38



In-Finity 35 Suspension Up & Down Emergency 3000K General Lighting

■ N35UEM3G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2663 |
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 46W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | | | |
|--------------------|------------------|--------------------|-----|
| Lighting type | Indirect, Direct | Beam angle C90-270 | 110 |
| LED type | Top LED | (°) | |
| Light distribution | Symmetric | | |
| Optical type | Diffused light | | |
| Beam angle (°) | 110 | | |

Electrical

| | | | |
|-------------|--------------|------------------|---|
| Voltage (V) | 220.00 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | With | | |

Physical

| | |
|-------------|---------------|
| Color | Anodized Grey |
| Orientation | Fixed |
| Weight (kg) | 3.19 |
| Length (mm) | 1405 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down Emergency 3000K General Lighting



Power supply rose
08.0031.00



Metal cover. Suspension Up & Down.
35 mm (Colour Black)
08.9056.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00



Metal cover. Suspension Up & Down.
35 mm
08.9056.06



Metal cover. Suspension Up & Down.
35 mm (Colour Anodized Grey)
08.9056.02



Metal cover. Suspension Up & Down.
35 mm (Colour White)
08.9056.40



Suspension kit
08.0030