





N35UFC3U02B - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	1838
Lamp category	LED	Mountings	Suspension
Power (W)	36.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 76
Beam angle C90-270 (°) 64



Luminous flux luminaire 1838 lm

Beam /	Ang l e DIR:	: 75°
h(m)	E(lx)	D(m)
1	662	1.25
2	166	2.50
3	74	3.76
4	41	5.01
5	26	6.26

· /



·			
Electrical			
Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	1

Non Dimmable

No Integrated

Physical

Dimmable

Driver

Color	Anodized Gre	
Orientation	Fixed	
Weight (kg)	3.16	
Length (mm)	568	

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down Flat Corner 3000K Micro-Prismatic Diffuser



Metal cover. Suspension Up & Down. 35 mm 08.9056.06



Metal cover. Suspension Up & Down. 35 mm (Colour Black) 08.9056.NS



Suspension kit 08.0030



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Power supply rose 08.0031.00



Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02



Metal cover. Suspension Up & Down. 35 mm (Colour White)

