



# In-Finity 35 Suspension Up & Down Flat Corner 4000K General Lighting Dali

## N35UFC4G14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

#### Main specifications

Number of heads	1	Net lumen (lm)	2306
Lamp category	LED	Mountings	Suspension
Power (W)	36.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

### Optical

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Indirect, Direct Top LED Symmetric Diffused light 110 110



Beam Angle DIR: 107° h(m) E(lx) D(m) 1 523 2.63 2 131 5.26 3 58 7.90 4 33 10.53 5 21 13.16

Luminous flux luminaire 2306 lm

Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Integrated Dimmable DALI 1	Emergency Insulation class	Without I
Physical			
Color Orientation Weight (kg) Length (mm)	Black Fixed 3.16 568		

#### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Suspension Up & Down Flat Corner 4000K General Lighting Dali



Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02 Metal cover. Suspension Up & Down. 35 mm (Colour White) 08.9056.40 Suspension kit 08.0030







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00 Metal cover. Suspension Up & Down. 35 mm 08.9056.06

Metal cover. Suspension Up & Down. 35 mm (Colour Black) 08.9056.NS



Power supply rose. Dali 08.0031.00.DA