

## In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser Dali

■ N35UFC4U02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1990                |
| Lamp category   | LED   | Mountings      | Suspension          |
| Power (W)       | 36.5W | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 80    |                |                     |

### Optical

|                        |                  |
|------------------------|------------------|
| Lighting type          | Indirect, Direct |
| LED type               | Top LED          |
| Light distribution     | Symmetric        |
| Optical type           | Diffused light   |
| Beam angle (°)         | 76               |
| Beam angle C90-270 (°) | 64               |



Beam Angle DIR: 75°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 717   | 1.25 |
| 2    | 179   | 2.50 |
| 3    | 80    | 3.76 |
| 4    | 45    | 5.01 |
| 5    | 29    | 6.26 |

Luminous flux luminaire  
1990 lm

### Electrical


|                |               |                  |         |
|----------------|---------------|------------------|---------|
| Frequency (Hz) | 50/60         | Emergency        | Without |
| Voltage (V)    | 220.00        | Insulation class | I       |
| Dimmable       | Yes           |                  |         |
| Driver         | Integrated    |                  |         |
| Driver type    | Dimmable DALI |                  |         |
|                | 1             |                  |         |

### Physical

|             |               |
|-------------|---------------|
| Color       | Anodized Grey |
| Orientation | Fixed         |
| Weight (kg) | 3.16          |
| Length (mm) | 568           |

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser Dali



500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0112.00



Metal cover. Suspension Up & Down.  
35 mm (Colour Anodized Grey)  
08.9056.02



Metal cover. Suspension Up & Down.  
35 mm (Colour White)  
08.9056.40



Power supply rose. Dali  
08.0031.00.DA



Suspension kit  
08.0030



Metal cover. Suspension Up & Down.  
35 mm  
08.9056.06



Metal cover. Suspension Up & Down.  
35 mm (Colour Black)

