





In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser

N35UFC4U02B - Anodized Grey


 ${\sf LED\ modular\ system\ for\ suspended\ installation, including\ LED\ luminaires, aluminum\ installation\ profile, and}$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

| Number of heads | 1 | Net lumen (lm) | 1990 |
|-----------------|-------|----------------|---------------------|
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 36.5W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

Indirect, Direct Lighting type LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 76 Beam angle C90-270 (°) 64



| H | 1 | 717 | 1.25 |
|-------------|---|-----|------|
|) | 2 | 179 | 2.50 |
| H | 3 | 80 | 3.76 |
| \setminus | 4 | 45 | 5.01 |
| 5°, | 5 | 29 | 6.26 |

Beam Angle DIR:

h(m)

 $E(I_X)$

75°

D(m)

| Luminous tlu | x luminaire |
|--------------|-------------|
| 1990 lm | |
| | |

| 1/256 | [] [S] [S] [S] [S] [S] [S] [S] [S] [S] [|
|-------|--|

| 3 03 | F | I P 20 | EHE CE RETILAP |
|-------------|----------|---------------|----------------|
| GWT 850° | | | |

Electrical

| Frequency (Hz) | 50/60 | Emergency | Without |
|----------------|------------|------------------|---------|
| Voltage (V) | 220.00 | Insulation class | 1 |
| Dimmable | No | | |
| Driver | Integrated | | |

Non Dimmable

Driver type Physical

| Color | Anodized Gre | |
|-------------|--------------|--|
| Orientation | Fixed | |
| Weight (kg) | 3.16 | |
| Length (mm) | 568 | |

Note

 ${\bf Micro-Prismatic\ Diffuser:\ Highly\ efficient\ multilayer\ diffuser\ that,\ thanks\ to\ its\ unique\ micro-prismatic\ texture,}$ $provides\ a\ glare\ free\ UGR<19\ light\ beam.\ /\ Emergency:\ Emergency\ Module\ available\ in\ all\ versions,\ length\ 1405$ mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00

Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02

Metal cover. Suspension Up & Down. 35 mm (Colour White) 08.9056.40







Suspension kit 08.0030

Power supply rose 08.0031.00

Metal cover. Suspension Up & Down. 35 mm 08.9056.06



Metal cover. Suspension Up & Down. 35 mm (Colour Black)

