

## In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser

■ N35UFC4U30B - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1990
<b>Lamp category</b>	LED	<b>Mountings</b>	Suspension
<b>Power (W)</b>	36.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical


<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	76
<b>Beam angle C90-270 (°)</b>	64



Beam Angle DIR: 75°

h(m)	E(lx)	D(m)
1	717	1.25
2	179	2.50
3	80	3.76
4	45	5.01
5	29	6.26

Luminous flux luminaire  
1990 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	3.16
<b>Length (mm)</b>	568



### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser



5

Metal cover. Suspension Up & Down.  
35 mm (Colour Anodized Grey)  
08.9056.02



5

Metal cover. Suspension Up & Down.  
35 mm (Colour Black)  
08.9056.NS



5

Metal cover. Suspension Up & Down.  
35 mm  
08.9056.06



500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0112.00



Power supply rose  
08.0031.00



5

Metal cover. Suspension Up & Down.  
35 mm (Colour White)  
08.9056.40



Suspension kit  
08.0030