


In-Finity 70 Recessed Trim 3000K General Lighting

■ N70T113G14B - Black

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




Main specifications

Lamp category	LED	Mountings	Recessed
Power (W)	23.1W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	2524		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Beam Angle: 102°

h(m)	E(lx)	D(m)
1	957	2.45
2	239	4.90
3	106	7.34
4	60	9.79
5	38	12.24

Luminous flux luminaire
2524 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	5
Length (mm)	1125

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Recessed Trim 3000K General Lighting



5

Metal cover. Recessed Trim. 70 mm
(Colour Black)
08.9053.NS



5

Metal cover. Recessed Trim. 70 mm
(Colour Anodized Grey)
08.9053.02



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0110.00



5

Metal cover. Recessed Trim. 70 mm
(Colour White)
08.9053.40