

In-Finity 70 Recessed Trim 3000K General Lighting

LED

N70T253G30B - White

 ${\tt LED\ modular\ system\ for\ recessed\ Trim\ installation, including\ LED\ luminaires, aluminum\ installation\ profile\ and\ profile\ p$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Main specifications

Lamp category	LLD
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	5680

Mountings Environment Recessed Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire 5680 lm

Insulation class

Beam Angle:		102°
h(m)	E(lx)	D(m)
1	2154	2.45
2	538	4.90
3	239	7.34
4	135	9.79
5	86	12.24

Electrical

rrequency (mz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	11
Length (mm)	2530

Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Recessed Trim 3000K General Lighting







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal cover. Recessed Trim. 70 mm (Colour White) 08.9053.40

Metal cover. Recessed Trim. 70 mm (Colour Black) 08.9053.NS



Metal cover. Recessed Trim. 70 mm (Colour Anodized Grey) 08.9053.02