







In-Finity 70 Recessed Trim 3000K Micro-Prismatic Diffuser N70T053U02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications						
Lamp category Power (W) CCT (K) CRI Net lumen (Im)	LED 23.1W/m 3000K 80 755	Mountings Environment	Recessed Indoor dry I	ocation		
Optical						
Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 67 76	90°	90°	Beam A	Ang l e:	67°
				h(m)	E(lx)	D(m)
				1	490	1.33
				2	123	2.66
				3	54	3.99
				4	31	5.32
		30° / 490 cd	<u>30°</u>	5	20	6.65
		Luminous flux lu 755 lm	iminaire			
Electrical						
Frequency (Hz) Dimmable Driver Driver type Emergency	50/60 No Integrated Non Dimmable Without	Insulation class	I			
Physical						
Color Orientation Recessed depth (mm) Weight (kg) Length (mm)	Anodized Grey Fixed 135 3.60 565					

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Recessed Trim 3000K Micro-Prismatic Diffuser







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00 Metal cover. Recessed Trim. 70 mm (Colour Anodized Grey) 08.9053.02 Metal cover. Recessed Trim. 70 mm (Colour Black) 08.9053.NS



Metal cover. Recessed Trim. 70 mm (Colour White) 08.9053.40