

In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser Dali

■ N70T254U02BDA - Anodized Grey


LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications

Lamp category	LED	Mountings	Recessed
Power (W)	23.1W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		
Net lumen (lm)	3680		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Beam Angle: 67°

h(m) E(lx) D(m)

1 2389 1.33

2 597 2.66

3 265 3.99

4 149 5.32

5 96 6.65

Luminous flux luminaire
3680 lm

Electrical




Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
Emergency	Without		

Physical

Color	Anodized Grey
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	11
Length (mm)	2530

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser Dali



5

Metal cover. Recessed Trim. 70 mm
(Colour Anodized Grey)
08.9053.02



5

Metal cover. Recessed Trim. 70 mm
(Colour Black)
08.9053.NS



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0113.00



5

Metal cover. Recessed Trim. 70 mm
(Colour White)
08.9053.40