

### In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser

■ N70T054U30B - White


LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

#### Main specifications

|                       |         |                    |                     |
|-----------------------|---------|--------------------|---------------------|
| <b>Lamp category</b>  | LED     | <b>Mountings</b>   | Recessed            |
| <b>Power (W)</b>      | 23.1W/m | <b>Environment</b> | Indoor dry location |
| <b>CCT (K)</b>        | 4000K   |                    |                     |
| <b>CRI</b>            | 80      |                    |                     |
| <b>Net lumen (lm)</b> | 818     |                    |                     |

#### Optical

|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Direct         |
| <b>LED type</b>               | Top LED        |
| <b>Light distribution</b>     | Symmetric      |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 67             |
| <b>Beam angle C90-270 (°)</b> | 76             |



Beam Angle: 67°

h(m) E(lx) D(m)

1 531 1.33

2 133 2.66

3 59 3.99

4 33 5.32

5 21 6.65

Luminous flux luminaire  
818 lm

#### Electrical




|                       |              |                         |   |
|-----------------------|--------------|-------------------------|---|
| <b>Frequency (Hz)</b> | 50/60        | <b>Insulation class</b> | I |
| <b>Dimmable</b>       | No           |                         |   |
| <b>Driver</b>         | Integrated   |                         |   |
| <b>Driver type</b>    | Non Dimmable |                         |   |
| <b>Emergency</b>      | Without      |                         |   |

#### Physical

|                            |       |
|----------------------------|-------|
| <b>Color</b>               | White |
| <b>Orientation</b>         | Fixed |
| <b>Recessed depth (mm)</b> | 135   |
| <b>Weight (kg)</b>         | 3.60  |
| <b>Length (mm)</b>         | 565   |

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



## In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser



5

---

Metal cover. Recessed Trim. 70 mm  
(Colour Anodized Grey)  
08.9053.02



5

---

Metal cover. Recessed Trim. 70 mm  
(Colour Black)  
08.9053.NS



---

500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0113.00



5

---

Metal cover. Recessed Trim. 70 mm  
(Colour White)  
08.9053.40