



## In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser

### ■ N70T084U02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	23.1W/m	<b>Environment</b>	Indoor
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		
<b>Net lumen (lm)</b>	1227		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	67
<b>Beam angle C90-270 (°)</b>	76



<b>Beam Angle:</b>	67°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	796	1.33	
2	199	2.66	
3	88	3.99	
4	50	5.32	
5	32	6.65	

Luminous flux luminaire  
1227 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Anodized Grey
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	135
<b>Weight (kg)</b>	4.30
<b>Length (mm)</b>	845

### Certification / Marking



### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 70 Recessed Trim 4000K Micro-Prismatic Diffuser



5



5



5

---

Metal cover. Recessed Trim. 70 mm  
(Colour Anodized Grey)  
08.9053.02

Metal cover. Recessed Trim. 70 mm  
(Colour Black)  
08.9053.NS

Metal cover. Recessed Trim. 70 mm  
(Colour White)  
08.9053.40



---

500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0113.00