

In-Finity 70 Recessed Trim Emergency 4000K Micro-Prismatic Diffuser

N70TEM4U02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications

Lamp category	LED	**Environment**	Indoor dry location
Power (W)	23.1W/m		
CCT (K)	4000K		
CRI	80		
Mountings	Recessed		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	72

Electrical

Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without
Insulation class	I

Physical

Color	Anodized Grey
Orientation	Fixed
Recessed depth (mm)	135
Length (mm)	1400

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Recessed Trim Emergency 4000K Micro-Prismatic Diffuser

5

Metal cover. Recessed Trim. 70 mm
(Colour Anodized Grey)
08.9053.02

5

Metal cover. Recessed Trim. 70 mm
(Colour Black)
08.9053.NS

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam
08.0113.00

5

Metal cover. Recessed Trim. 70 mm
(Colour White)
08.9053.40