



## In-Finity 70 Recessed Trim Flat Corner 4000K Micro-Prismatic Diffuser Dali

■ N70TFC4U02BDA - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




### Main specifications

|                        |         |                       |          |
|------------------------|---------|-----------------------|----------|
| <b>Number of heads</b> | 1       | <b>Net lumen (lm)</b> | 1636     |
| <b>Lamp category</b>   | LED     | <b>Mountings</b>      | Recessed |
| <b>Power (W)</b>       | 23.1W/m | <b>Environment</b>    | Indoor   |
| <b>CCT (K)</b>         | 4000K   |                       |          |
| <b>CRI</b>             | 80      |                       |          |

### Optical

|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Direct         |
| <b>LED type</b>               | Top LED        |
| <b>Light distribution</b>     | Symmetric      |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 67             |
| <b>Beam angle C90-270 (°)</b> | 76             |



|                    |             |              |             |
|--------------------|-------------|--------------|-------------|
| <b>Beam Angle:</b> | 67°         |              |             |
|                    | <b>h(m)</b> | <b>E(lx)</b> | <b>D(m)</b> |
| 1                  | 1062        | 1.33         |             |
| 2                  | 265         | 2.66         |             |
| 3                  | 118         | 3.99         |             |
| 4                  | 66          | 5.32         |             |
| 5                  | 42          | 6.65         |             |

Luminous flux luminaire  
1636 lm

### Electrical

|                         |            |
|-------------------------|------------|
| <b>Frequency (Hz)</b>   | 50/60      |
| <b>Dimmable</b>         | Yes        |
| <b>Driver</b>           | Integrated |
| <b>Emergency</b>        | Without    |
| <b>Insulation class</b> | I          |

### Physical

|                            |               |
|----------------------------|---------------|
| <b>Color</b>               | Anodized Grey |
| <b>Orientation</b>         | Fixed         |
| <b>Recessed depth (mm)</b> | 135           |
| <b>Weight (kg)</b>         | 4.10          |

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 70 Recessed Trim Flat Corner 4000K Micro-Prismatic Diffuser Dali



5



5

---

500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0113.00

Metal cover. Recessed Trim. 70 mm  
(Colour Anodized Grey)  
08.9053.02

Metal cover. Recessed Trim. 70 mm  
(Colour Black)  
08.9053.NS



5

---

Metal cover. Recessed Trim. 70 mm  
(Colour White)  
08.9053.40