In-Finity 70 Surface 3000K General Lighting Dali

N70S303G02BDA - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.





Main specifications

Lamp category	LED	**Mountings**	Surface
Power (W)	23.1W/m	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	6942		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire
6942 lm

Beam Angle: 102°

h(m)	E(lx)	D(m)
1	2632	2.45
2	658	4.90
3	292	7.34
4	165	9.79
5	105	12.24

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	13.6
Length (mm)	3095

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface 3000K General Lighting Dali

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0110.00

Metal cover. Surface / Suspension Down. 70 mm
08.9052.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey)
08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black)
08.9052.NS

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White)
08.9052.40