


In-Finity 70 Surface 3000K General Lighting

□ **N70S053G30B - White**

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



108
69
73




Main specifications

Lamp category	LED	Mountings	Surface
Power (W)	23.1W/m	Environment	Indoor
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	1262		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Beam Angle: 102°

h(m)	E(lx)	D(m)
1	479	2.45
2	120	4.90
3	53	7.34
4	30	9.79
5	19	12.24

Luminous flux luminaire
1262 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	3.60
Length (mm)	565

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface 3000K General Lighting



5

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 70 mm
(Colour White)
08.9052.40



5

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 70 mm
(Colour Anodized Grey)
08.9052.02



5

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 70 mm
(Colour Black)
08.9052.NS



5

Metal cover. Surface / Suspension
Down. 70 mm
08.9052.06



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0110.00