Surface


Indoor dry location













In-Finity 70 Surface 3000K General Lighting

N70S193G02B - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Lamp category	LED	Mountings
Power (W)	23.1W/m	Environment
CCT (K)	3000K	
CRI	80	

4417

Optical

Net lumen (lm)

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Insulation class

Beam	Beam Angle:	
h(m)	E(lx)	D(m
1	1675	2.45
2	419	4.90
3	186	7.34
4	105	9.79
5	67	12.24

Electrical

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	8.10
Length (mm)	1970

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface 3000K General Lighting



Metal cover. Surface / Suspension Down. 70 mm 08.9052.06

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40