



In-Finity 70 Surface 3000K General Lighting

LED

N70S193G30B - White

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main s	pecifications
--------	---------------


Lamp category	LLD
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	4417

Mountings Surface Environment

Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Insulation class

Beam	Beam Angle:	
h(m)	E(l ×)	D(m)
1	1675	2.45
2	419	4.90
3	186	7.34
4	105	9.79
5	67	12.24

Luminous	flux	luminaire
4417 lm		

Electrical

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

Color	White
Orientation	Fixed
Weight (kg)	8.10
Length (mm)	1970

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface 3000K General Lighting





FLOS 5



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40





500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06