



In-Finity 70 Surface 4000K General Lighting

■ N70S164G14B - Black

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications
Lamp category


Lamp category	LED
Power (W)	23.1W/m
CCT (K)	4000K
CRI	80
Net lumen (lm)	4100

Surface Mountings

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire 4100 lm

Insulation class

Bean	n Angle:	102°
h(m)	E(lx)	D(m)
1	1555	2.45
2	389	4.90
3	173	7.34
4	97	9.79
5	62	12.24

Electrical

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical


Color	Black
Orientation	Fixed
Weight (kg)	7.40
Length (mm)	1690

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface 4000K General Lighting







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00



Metal cover. Surface / Suspension Down. 70 mm 08.9052.06