



# In-Finity 70 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser Dali

# N70SDC3U02BDA - Anodized Grey


LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### Main specifications

Number of heads	1	Net lumen (lm)	1511
Lamp category	LED	Mountings	Surface
Power (W)	23.1W/m	Environment	Indoor dry location
CCT (K)	3000K		
CDI	00		

#### Optical

Direct
Top LED
Symmetric
Diffused light
67
76



1	980	1.33
2	245	2.66
3	109	3.99
4	61	5.32
5	39	6.65

Beam Angle:

67°

D(m)

Luminous flux luminaire 1511 lm

Liecuicai		
Frequency (Hz)	50/60	Insulation class
Dimmoble	Vaa	

Driver Integrated
Driver type Dimmable DALI

**Emergency** Without

## Physical

 Color
 Anodized Grey

 Orientation
 Fixed


 Weight (kg)
 4.10

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 70 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40