



In-Finity 70 Surface Dihedral Corner 4000K General Lighting

N70SDC4G02B - Anodized Grey


LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications

Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	23.1W/m	Environment
CCT (K)	4000K	
CRI	80	

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Insulation class

3 115 7.34 4 65 9.79 5 41 12.24

2733

Surface

Indoor dry location

Beam Angle: 102°

E(Ix)

1036

259

D(m)

2.45

4.90

h(m)

2

Editilious liux i
2733 lm

Electrical

rrequency (nz)	30/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	4.10

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface Dihedral Corner 4000K General Lighting








500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40