



# In-Finity 70 Surface Dihedral Corner 4000K Micro-Prismatic Diffuser Dali

### N70SDC4U02BDA - Anodized Grey


LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

#### Main specifications

Number of heads	1	Net lumen (lm)	1636
Lamp category	LED	Mountings	Surface
Power (W)	23.1W/m	Environment	Indoor dry location
CCT (K)	4000K		
CDI	00		

#### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Insulation class

h(m)	E(lx)	D(m)
1	1062	1.33
2	265	2.66
3	118	3.99
4	66	5.32
5	42	6.65

Beam Angle:

Luminous tlux	luminaire
1636 lm	

	• <b>.</b>	
-	loctrico I	
_	lectrical	

Frequency (Hz)

Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DAL
	1
Emergency	Without

50/60

#### **Physical**

Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	4.10	

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 70 Surface Dihedral Corner 4000K Micro-Prismatic Diffuser Dali








500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS







Metal cover. Surface / Suspension Down. 70 mm 08.9052.06