



In-Finity 70 Surface Emergency 3000K General Lighting Dali

light

■ N70SEM3G14BDA - Black

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Main s	pecifications
--------	---------------

Lamp category	LED
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	3155

Mountings Environment Surface Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetri
Optical type	Diffused
Beam angle (°)	102



Luminous flux luminaire 3155 lm

Beam Angle:		102°
h(m)	E(lx)	D(m)
1	1197	2.45
2	299	4.90
3	133	7.34
4	75	9.79
5	48	12.24

Electrical

Frequency (Hz)	50/60
Voltage (V)	46.50
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Insulation class

Emergency

Without

Physical

Color	Black
Orientation	Fixed
Weight (kg)	6.60
Length (mm)	1400

Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Surface Emergency 3000K General Lighting Dali



Metal cover. Surface / Suspension Down. 70 mm 08.9052.06

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40