


## In-Finity 70 Surface Emergency 3000K General Lighting

### ■ N70SEM3G02B - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



108  
69  
73

### Main specifications

<b>Lamp category</b>	LED	<b>Environment</b>	Indoor dry location
<b>Power (W)</b>	23.1W/m		
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		
<b>Mountings</b>	Surface		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	103

### Electrical

<b>Dimmable</b>	No
<b>Driver</b>	Integrated
<b>Driver type</b>	Non Dimmable
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	Anodized Grey
<b>Orientation</b>	Fixed
<b>Length (mm)</b>	1400

### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



## In-Finity 70 Surface Emergency 3000K General Lighting



5

Metal cover. Surface / Suspension  
Down. 70 mm  
08.9052.06



5

Metal End Cap. Recessed No Trim /  
Surface / Suspension Down. 70 mm  
(Colour Anodized Grey)  
08.9052.02



500 mm opal diffuser. Diffuse, glare  
free and uniform lighting throughout  
the room  
08.0110.00



5

Metal End Cap. Recessed No Trim /  
Surface / Suspension Down. 70 mm  
(Colour White)  
08.9052.40



5

Metal End Cap. Recessed No Trim /  
Surface / Suspension Down. 70 mm  
(Colour Black)  
08.9052.NS