





N70D083G02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.


Main specifications


Lamp category	LED
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	1893

Mountings Environment Suspension Indoor dry location












Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused ligh
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire 1893 lm

Insulation class

Beam Angle:		102°
h(m)	E(lx)	D(m)
1	718	2.45
2	179	4.90
3	80	7.34
4	45	9.79
5	29	12 24

Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
•	1

Emergency Without

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	4.30
Lenath (mm)	845

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K General Lighting Dali



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS





5

Suspension kit 08.0030

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White)

