


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

LED
23.1W/m
3000K
80
2524


Mountings Environment Suspension Indoor dry location







•	
Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused ligh
Beam angle (°)	102
Beam angle C90-270 (°)	106



 $E(I_X)$ h(m) D(m) 957 2.45 2 239 4.90 3 106 7.34 4 60 9.79 38 12.24

Beam Angle: 102°

Luminous flux luminaire 2524 lm

_	ACTION.
	lectrica

Optical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Black
Fixed
5
1125

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K General Lighting Dali



Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00



Power supply rose. Dali 08.0031.00.DA