





LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	3155


Mountings Environment Suspension Indoor dry location







•	
ighting type	Direct
LED type	Top LED
ight distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Insulation class

Beam Angle:		102°
h(m)	E(lx)	D(m
1	1197	2.45
2	299	4.90
3	133	7.34
4	75	9.79
5	48	12.24

Luminous flux luminair 3155 lm

50/60

E	lec	trie	ca	l
Fr	eau	en	cv	(H:

Optical

Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

White
Fixed
6.60
1405

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K General Lighting







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS







Power supply rose 08.0031.00

Suspension kit 08.0030

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40