

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	1511

Mountings Environment

1511 lm

Insulation class


Suspension Indoor dry location





/#Z/00	\F7	IP	COL	((RETILAP
A 100		20	CUL	7	KETIDAI
014/7					

Optical	
Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



600	1	980	1.33
~]	2	245	2.66
\times	3	109	3.99
	4	61	5.32
30°	5	39	6.65

Beam Angle:

h(m) = E(Ix)

67°

D(m)

Electrical

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical


Color	Anodized Grey		
Orientation	Fixed		
Weight (kg)	5		
Length (mm)	1125		

Note

 $Micro-Prismatic \ Diffuser: Highly \ efficient \ multilayer \ diffuser \ that, thanks \ to \ its \ unique \ micro-prismatic \ texture,$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K Micro-Prismatic Diffuser







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00



Suspension kit 08.0030



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim /

(Colour Black)				
08.9052.NS				
ttns://www.flos.com/professional-space/ar	ahitaatural/araduata/ia fiaitu	70 30001	nioro priomatio diffusor	www.flos.com - info@flos.co