

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications


Lamp category	LED	
Power (W)	23.1W/m	
CCT (K)	3000K	
CRI	80	
Net lumen (lm)	2266	

MountingsSuspensionEnvironmentIndoor dry location





Lighting type Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 67
Beam angle C90-270 (°) 76



30° 1471 cd 30° 5 Luminous flux luminaire 2266 lm

Beam Angle:		67°
h(m)	E(l x)	D(m)
1	1471	1.33
2	368	2.66
3	163	3.99
4	92	5.32
5	59	6.65

L	

[] [69 73

Electrical

Optical

rrequericy (112)	30/00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Frequency (Hz) 50/60 Insulation class

Physical

Color	Anodized Gre		
Orientation	Fixed		
Weight (kg)	7.40		
Length (mm)	1690		


IP 20 FHI CE RETILAP

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K Micro-Prismatic Diffuser







Suspension kit 08.0030



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Metal End Cap. Recessed No Trim /

(Colour White) 08.9052.40		