

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.


Main specifications

Lamp category	LED
Power (W)	23.1W/m
CCT (K)	3000K
CRI	80
Net lumen (lm)	3399

Mountings Suspension Environment Indoor dry location



Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Luminous flux luminaire 3399 lm

Beam Angle:		67°
h(m)) E(l ×)	D(m)
1	2206	1.33
2	552	2.66
3	245	3.99
4	138	5.32
5	88	6.65

Electrical		
Frequency (Hz)	50/60	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	
Emergency	Without	



3 603	[\\[\bar{\pi} \]	20	tHL	CE	RETILAP
GWT 850°		<u>_</u>			

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	11
Length (mm)	2530

Note

 $Micro-Prismatic \ Diffuser: Highly \ efficient \ multilayer \ diffuser \ that, thanks \ to \ its \ unique \ micro-prismatic \ texture,$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 3000K Micro-Prismatic Diffuser



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40



500 mm micro-prismatic diffuser.

that, thanks to its unique

08.0113.00

Highly efficient multilayer diffuser

microprismatic texture, provides a glare free UGR<19 light beam

FLOS 5

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Suspension kit 08.0030



Power supply rose

