





In-Finity 70 Suspension Down 4000K General Lighting Dali

N70D084G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.


Main specifications

LED
23.1W/m
4000K
80
2050

Mountings Environment Suspension Indoor dry location



Direct
Top LED
Symmetric
Diffused light
102
106



h(m) E(lx)D(m) 777 2.45 2 194 4.90 3 7.34 86 4 9.79 31 12.24

Beam Angle: 102°

Luminous flux luminaire 2050 lm

E	ectrical
_	CCUICUI

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
	1

Without

Insulation class



Emergency Physical

Color	White
Orientation	Fixed
Weight (kg)	4.30
Length (mm)	845

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 4000K General Lighting Dali







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS







Suspension kit 08.0030

Power supply rose. Dali 08.0031.00.DA

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40