



In-Finity 70 Suspension Down 4000K Micro-Prismatic Diffuser Dali

N70D194U30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications


| Lamp category | LED | Mountings | Suspension |
|---------------|---------|-------------|---------------------|
| Power (W) | 23.1W/m | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

2862

Optical

Net lumen (lm)

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 67 Beam angle C90-270 (°) 76



| <u> </u> | | | | | |
|----------|--------|------|----|------|-----|
| Lumin | ous fl | ux l | um | nina | ire |
| 2862 In | n | | | | |

Insulation class

| Bean | Beam Angle: | |
|------|-------------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1858 | 1.33 |
| 2 | 464 | 2.66 |
| 3 | 206 | 3.99 |
| 4 | 116 | 5.32 |
| 5 | 74 | 6.65 |

Electrical

| Frequency (Hz) | 50/60 |
|----------------|---------------|
| Dimmable | Yes |
| Driver | Integrated |
| Driver type | Dimmable DALI |
| | 1 |

Emergency Without

Physical

| Color | White |
|-------------|-------|
| Orientation | Fixed |
| Weight (kg) | 8.10 |
| Length (mm) | 1970 |
| | |

Note

 ${\bf Micro-Prismatic\ Diffuser:\ Highly\ efficient\ multilayer\ diffuser\ that,\ thanks\ to\ its\ unique\ micro-prismatic\ texture,}$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down 4000K Micro-Prismatic Diffuser Dali



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique

| glare free UGR<19 light beam 08.0113.00 | | |
|---|-----------------------------|---------------------------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| ttps://www.flos.com/professional-space/architectural/products/in-finity-70-suspension-down-4000 | lk micro priematic diffusor | www.flos.com_info@flos.co |