



In-Finity 70 Suspension Down Emergency 3000K General Lighting Dali

■ N70DEM3G14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED	Mountings	Suspension
Power (W)	23.1W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	3155		

Optical

Lighting type Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 102
Beam angle C90-270 (°) 106



Beam Angle:		102°
h(m)	E(lx)	D(m)
1	1197	2.45
2	299	4.90
3	133	7.34
4	75	9.79
5	48	12.24

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	46.50	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	6.60
Length (mm)	1400

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down Emergency 3000K General Lighting Dali







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS







Suspension kit 08.0030

Power supply rose. Dali 08.0031.00.DA

Metal cover. Surface / Suspension Down. 70 mm 08.9052.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White)

08.9052.40