



18  
69  
73



## In-Finity 70 Suspension Down Emergency 3000K General Lighting

### ■ N70DEM3G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

#### Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	23.1W/m		
CCT (K)	3000K		
CRI	80		
Mountings	Suspension		

#### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103

#### Electrical

Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without
Insulation class	I

#### Physical

Color	Anodized Grey
Orientation	Fixed
Length (mm)	1400

#### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Down Emergency 3000K General Lighting



Suspension kit  
08.0030



Power supply rose  
08.0031.00



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0110.00



5

Metal cover. Surface / Suspension Down. 70 mm  
08.9052.06



5

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey)  
08.9052.02



5

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black)  
08.9052.NS



5

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White)  
08.9052.01

