









In-Finity 70 Suspension Down Emergency 3000K Micro-Prismatic Diffuser Dali

N70DEM3U02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications			
Lamp category Power (W) CCT (K) CRI Mountings	LED 23.1W/m 3000K 80 Suspension	Environment	Indoor dry location
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°)	Direct Top LED Symmetric Diffused light 72		
Electrical			
Dimmable Driver Driver type	Yes Integrated Dimmable DALI		
Emergency Insulation class	Without I		
Physical			
Color Orientation	Anodized Grey Fixed		

Note

Length (mm)

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

1400

In-Finity 70 Suspension Down Emergency 3000K Micro-Prismatic Diffuser Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour White) 08.9052.40

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Anodized Grey) 08.9052.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 70 mm (Colour Black) 08.9052.NS



Suspension kit 08.0030



Power supply rose. Dali 08.0031.00.DA



Metal cover. Surface / Suspension

