



In-Finity 70 Suspension Down Emergency 3000K Micro-Prismatic Diffuser

■ N70DEM3U14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	23.1W/m		
CCT (K)	3000K		
CRI	80		
Mountings	Suspension		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	72

Electrical

Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without
Insulation class	I

Physical

Color	Black
Orientation	Fixed
Length (mm)	1400

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Down Emergency 3000K Micro-Prismatic Diffuser



Suspension kit
08.0030



Power supply rose
08.0031.00



Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 70 mm
(Colour White)
08.9052.40



Metal cover. Surface / Suspension
Down. 70 mm
08.9052.06



Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 70 mm
(Colour Anodized Grey)
08.9052.02



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0113.00



Metal End Cap. Recessed No Trim /

(Colour Black)
08.9052.NS