

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

N70U143U14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	3508
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	3000K		·
CRI	80		

Optical

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Indirect, Direct Top LED Symmetric Diffused light 67 76



Beam	Ang l e D I R:	67°
h(m)	E(İ x)	D(m)
1	1226	1.33
2	306	2.66
3	136	3.99
4	77	5.32
5	49	6.65

Luminous flux luminaire 3508 lm

Electrical			
Frequency (Hz) Dimmable	50/60 Yes	Insulation class	Ι
Driver	Integrated		
Driver type	Dimmable DALI 1		
Emergency	Without		
Physical			
Color	Black		
Orientation	Fixed		
Weight (kg)	6.60		
Length (mm)	1405		

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali






Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40



500 mm micro-prismatic diffuser.

Highly efficient multilayer diffuser







Suspension kit 08.0030

Metal cover. Suspension Up & Down. 70 mm 08.9057.06

Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS



Power supply rose. Dali 08.0031.00.DA