

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

N70U143U30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	**Net lumen (lm)**	3508
Lamp category	LED	**Mountings**	Suspension
Power (W)	35.9W/m	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Luminous flux luminaire
3508 lm

Beam Angle DIR: 67°

h(m)	E(lx)	D(m)
1	1226	1.33
2	306	2.66
3	136	3.99
4	77	5.32
5	49	6.65

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	6.60
Length (mm)	1405

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

Suspension kit
08.0030

Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey)
08.9057.02

Metal cover. Suspension Up & Down. 70 mm (Colour White)
08.9057.40

Power supply rose. Dali
08.0031.00.DA

Metal cover. Suspension Up & Down. 70 mm
08.9057.06

Metal cover. Suspension Up & Down. 70 mm (Colour Black)
08.9057.NS

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam