



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

N70U163U02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	4210
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 67
Beam angle C90-270 (°) 76



4210 lm

Insulation class

901	2	368	2.66
	3	163	3.99
	4	92	5.32
2d 45°	5	59	6.65
ous flux luminaire			

Beam Angle DIR:

 $E(I_X)$

1471

D(m)

1.33

<u>h(</u>m)

_	lectrical
_	ecuica

Frequency (Hz) Dimmable	50/60 Yes
Driver	Integrated
Driver type	Dimmable DALI
Driver type	1

Emergency Without

Physical

Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	7.40	
Length (mm)	1690	

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali



Metal cover. Suspension Up & Down. 70 mm 08.9057.06



Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0113.00



Power supply rose. Dali 08.0031.00.DA