

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser

■ **N70U193U14B - Black**


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	4911
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Luminous flux luminaire
4911 lm

Beam Angle DIR: 67°

h(m)	E(lx)	D(m)
1	1716	1.33
2	429	2.66
3	191	3.99
4	107	5.32
5	69	6.65

Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	8.10
Length (mm)	1970

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser



Metal cover. Suspension Up & Down.
70 mm
08.9057.06

Metal cover. Suspension Up & Down.
70 mm (Colour Anodized Grey)
08.9057.02

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0110.00



Metal cover. Suspension Up & Down.
70 mm (Colour Black)
08.9057.NS

Power supply rose
08.0031.00

Suspension kit
08.0030



Metal cover. Suspension Up & Down.
70 mm (Colour White)
08.9057.40