



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser

N70U303U02B - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	7718
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 67
Beam angle C90-270 (°) 76



Beam	07	
h(m)	E(lx)	D(m)
1	2696	1.33
2	674	2.66
3	300	3.99
4	169	5.32
5	108	6.65

Electrical

50/60
No
Integrated
Non Dimmable
Without

Insulation class

Physical

Color	Anodized Gre	
Orientation	Fixed	
Weight (kg)	13.6	
Length (mm)	3095	

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Suspension kit 08.0030

Metal cover. Suspension Up & Down. 70 mm 08.9057.06



Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS



Power supply rose 08.0031.00



Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40