

In-Finity 70 Suspension Up & Down 4000K General Lighting Dali

■ N70U194G30BDA - White


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	7240
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire
7240 lm

Beam Angle DIR: 102°

h(m)	E(lx)	D(m)
1	1814	2.45
2	453	4.90
3	202	7.34
4	113	9.79
5	73	12.24

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	8.10
Length (mm)	1970

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 4000K General Lighting Dali



5

Metal cover. Suspension Up & Down.
70 mm
08.9057.06



5

Metal cover. Suspension Up & Down.
70 mm (Colour Black)
08.9057.NS



Suspension kit
08.0030



5

Metal cover. Suspension Up & Down.
70 mm (Colour Anodized Grey)
08.9057.02



5

Metal cover. Suspension Up & Down.
70 mm (Colour White)
08.9057.40



Power supply rose. Dali
08.0031.00.DA



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0110.00