



In-Finity 70 Suspension Up & Down 4000K Micro-Prismatic Diffuser

■ N70U194U14B - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	5318
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	4000K		·
CRI	80		

Optical

Lighting type Indirect, Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 67 Beam angle C90-270 (°) 76



_	\	/			,		_
L	um	inou	ıs fl	ux	lumi	nai	re
5	318	lm					

Beam	Angle DIR	: 67°
h(m)	E(lx)	D(m)
1	1858	1.33
2	464	2.66
3	206	3.99
4	116	5.32
5	74	6.65

Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	
Emergency	Without	

Physical

Color	Black
Orientation	Fixed
Weight (kg)	8.10
Length (mm)	1970

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, $provides\ a\ glare\ free\ UGR<19\ light\ beam.\ /\ Emergency:\ Emergency\ Module\ available\ in\ all\ versions,\ length\ 1405$ mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down 4000K Micro-Prismatic Diffuser







Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00



Power supply rose 08.0031.00



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40